



TRACK DAY & ROAD RACE TECHNICAL DATA*

LINE	POS	SIZE	SKU	PRICE	COMPOUND(S)	>>> DURABILITY >>>		REC. RIM	RIM RANGE	WIDTH†	DIA†	INFLATION PRESSURE (PSI)	
						Max Grip	Max Life					COLD	HOT
Q3+	F	110/70ZR17 (54W)	45036633	\$121.21	NA			3.0	2.5-3.5	110	591	33	35
	F	120/60ZR17 (55W)	45036351	\$119.72	NA			3.5	3.5-3.75	117	580	30-32	34-36
	F	120/70ZR17 (58)	45036891	\$123.27	NA			3.5	3.5-3.76	122	605	30-32	34-36
	R	150/60ZR17 (66W)	45036960	\$145.45	NA			4.0	3.5-4.0	150	617	24	26
	R	160/60ZR17 (69W)	45036196	\$147.91	NA			4.5	4.5-5.0	169	634	28-32	34-36
	R	180/55ZR17 (73W)	45036885	\$158.49	NA			5.5	5.5-6.0	187	636	28-32	34-36
	R	190/50ZR17 (73W)	45036411	\$180.32	NA			6.0	5.5-6.0	191	633	28-32	34-36
	R	190/55ZR17 (75W)	45036098	\$185.07	NA			6.0	5.5-6.0	194	650	28-32	34-36
Q4	F	120/70ZR17 (58W)	45233176	\$141.76	NA			3.5	3.5-3.75	121	604	30-32	34-36
	R	180/55ZR17 (73W)	45233177	\$182.27	NA			5.5	5.5-6.0	184	633	28-32	34-36
	R	180/60ZR17 (75W)	45233131	\$186.30	NA			5.5	5.0-5.5	189	658	28-32	34-36
	R	190/50ZR17 (73W)	45233060	\$207.36	NA			6.0	5.5-6.0	187	633	28-32	34-36
	R	190/55ZR17 (75W)	45233074	\$212.83	NA			6.0	5.5-6.0	194	649	28-32	34-36
	R	200/55ZR17 (78W)	45233092	\$252.76	NA			6.0	6.0-6.5	195	657	28-32	34-36
GP-A Pro	F	120/70ZR17 (58W)	45155801	\$155.00	7455			3.5	3.5-3.75	122	605	30-32	34-36
			45155727	\$155.00	8477								
	R	180/60R17 (75W)	45155176	\$235.00	0455			5.5	5.0-5.5	184	656	19-22	22-25
	R	190/60ZR17 (78W)	45155689	\$235.00	2662			5.5	5.5-6.0	190	657	18-22	22-25
			4515579	\$235.00	7455								
			45155041	\$235.00	7585								

Dunlop recommends that tire warmers be set at 70°-80°C for 45 minutes to 1 hour (maximum); tire performance degradation may occur if tires are subjected to repeated tire warming cycles, and/or temperatures/times in excess of these.

(*) Excluding Daytona

(†) Measured on recommended rim

THIS IS A PAGE BREAK - DO NOT DELETE



NON-DOT ROAD RACE TECHNICAL DATA*

LINE	POS	SIZE	SKU	PRICE	COMPOUND(S)	>>> DURABILITY >>>		REC. RIM	RIM RANGE	WIDTH†	DIA†	INFLATION PRESSURE (PSI)	
						Max Grip	Max Life					COLD	HOT
								(Inches)	(MM)				
KR448	F	110/70R17	45098128	\$145.00	0129			3.0	2.5-3.5	108	593	32-36	34-38
	F		45098176	\$155.00	0129			3.5	3.5-3.75	117	608	30-32	34-36
		45098107	\$155.00	2662									
		45098648	\$155.00	7455									
		45098889	\$155.00	8477									
KR106	F	120/80R420 16.5"	45030539	\$179.00	SOFT			3.5	3.5-3.75	122	602	30-33	34-36
KR451	R	140/70R17	45069412	\$200.00	0129			4.0	3.5-4.0	140	628	26-28	30-32
			45069332	\$200.00	0455								
	R	165/55R17	45069810	\$215.00	0197			5.0	4.5-5.25	165	629	26-28	30-32
			45069492	\$215.00	0455								
KR451	R	180/60R17	45069054	\$240.00	0197			5.5	5.0-5.5	184	656	19-22	22-25
			45069381	\$240.00	0129								
			45069117	\$240.00	0097								
			45069223	\$240.00	0455								
			45069616	\$240.00	0585								
KR451	R	200/55R17	45069322	\$240.00	0097			6.0	6.0-6.25	196	656	19-22	22-25
			45069748	\$240.00	0455								
			45069648	\$240.00	0585								
	R	200/60R17	45069128	\$245.00	0197			6.0	6.0-6.25	194	671	19-22	22-25
			45069918	\$245.00	0129								
			45069181	\$245.00	0097								
			45069227	\$245.00	0455								
			45069411	\$245.00	0585								
MOTO 3	F	90/80R17	45228947	\$125.00	SOFT			2.5	2.15-2.5	88	578	26-28	30-33
	R	115/75R17	45228008	\$145.00	SOFT			3.5	2.75-3.5	113	601	28-30	30-33
KR189 (WET)	F	95/70R17	45001699	\$125.00	WA			2.5	2.15-2.5	88	576	26-28	NA
		110/70R17	45001788	\$150.00	WA			3.0	2.75-3.5	116	588	30-33	NA
		120/70R17	45001565	\$155.00	WA			3.5	3.5-3.75	120	600	31-35	NA
KR389 (WET)	R	115/70R17	45118388	\$145.00	WA			3.5	2.75-3.5	116	600	28-33	NA
		140/65R17	45118937	\$180.00	WA			4.0	3.5-4.5	140	620	30-33	NA
KR404 (WET)	R	175/60R17	45024484	\$235.00	WA			5.5	5.5-6.0	174	636	30-33	NA
	R	185/60R17	45024890	\$240.00	WA			6.0	5.5-6.25	186	645	30-33	NA



Dunlop recommends that tire warmers be set at 70°-80°C for 45 minutes to 1 hour (maximum); tire performance degradation may occur if tires are subjected to repeated tire warming cycles, and/or temperatures/times in excess of these. Dunlop does not recommend the use of tire warmers on rain tires.

(*) Excluding Daytona

(⊕) Measured on recommended rim

THIS IS A PAGE BREAK - DO NOT DELETE

AMERICAN FLAT TRACK



LINE	POS	SIZE	SKU	PRICE	COMPOUND(S)	>>> DURABILITY >>>		REC. RIM	RIM RANGE	WIDTH⊕	DIA⊕	INFLATION PRESSURE (PSI)
						Max Grip	Max Life					
								(Inches)	(MM)	COLD**		
DT3	F	130/80-19	45041428	\$162.00	F5			3.0	2.25-3.0	131	683	1/4 Mile: 12-14 1/2 Mile: 16-24 1 Mile: 26-32
			45041555	\$178.00	R5							
	R	140/80-19	45041951	\$178.00	R8			3.5	2.75-3.5	149	704	
				45041194	\$178.00	R10						

** Optimum inflation pressure varies from track to track, depending upon track length, surface conditions and machine size.

Dunlop DT3 Flat Track tires are all 'Tube Type' and require the use of an inner tube, and rim band if tube-type rim.

Dunlop recommends that if tire warmers are used they are set at 70°-80°C for 45 minutes to 1 hour (maximum); tire performance degradation may occur if tires are subjected to repeated tire warming cycles, and/or temperatures/times in excess of these.

(⊕) Measured on recommended rim