

TRACK DAY & DOT ROAD RACE
TECHNICAL DATA



TIRE MODEL	POS	SIZE	COMPOUND(S)	DURABILITY		REC. RIM	RIM RANGE	WIDTH	DIA	INFLATION PRESSURE (PSI)	
				MAX GRIP	MAX LIFE					COLD	HOT
SPORTMAX Q5S	FRONT	110/70ZR17 (54W)	N/A			3.0	3.0-3.5	108	591	30-32	34-36
	FRONT	120/70ZR17 (58W)	N/A			3.5	3.5-3.75	122	598	30-32	34-36
	REAR	140/70ZR17 66W	N/A			3.8	3.75-4.5	141	628	30-32	34-36
	REAR	150/60ZR17 (66W)	N/A			4.25	4.25-4.5	155	616	28-32	34-36
	REAR	160/60ZR17 (69W)	N/A			4.5	4.5-5.0	161	634	28-32	34-36
	REAR	180/55ZR17 (73W)	N/A			5.5	5.5-6.0	186	635	28-32	34-36
	REAR	190/50ZR17 (73W)	N/A			6.0	5.5-6.25	191	633	28-32	34-36
	REAR	190/55ZR17 (75W)	N/A			6.0	5.5-6.25	194	648	28-32	34-36
	REAR	200/55ZR17 (78W)	N/A			6.25	6.0-6.5	202	658	28-32	34-36
SPORTMAX Q5	FRONT	110/70ZR17 (54W)	N/A			3.0	3.0-3.5	109	594	30-32	34-36
	FRONT	120/70ZR17 (58W)	N/A			3.5	3.5-3.75	119	607	30-32	34-36
	REAR	140/70ZR17 66W	N/A			3.8	3.75-4.5	136	628	28-32	34-36
	REAR	150/60ZR17 (66W)	N/A			4.3	4.25-4.5	145	618	28-32	34-36
	REAR	160/60ZR17 (69W)	N/A			4.5	4.5-5.0	160	635	28-32	34-36
	REAR	180/55ZR17 (73W)	N/A			5.5	5.5-6.0	180	633	28-32	34-36
	REAR	180/60ZR17 (75W)	N/A			5.0	5.0-6.0	183	658	28-32	34-36
	REAR	190/50ZR17 (73W)	N/A			6.0	5.5-6.25	191	635	28-32	34-36
	REAR	190/55ZR17 (75W)	N/A			6.0	5.5-6.25	193	653	28-32	34-36
	REAR	200/55ZR17 (78W)	N/A			6.3	6.0-6.5	201	658	28-32	34-36
	REAR	200/60ZR17 (80W)	N/A			5.5	5.5-6.25	193	672	28-32	34-36

Dunlop recommends that tire warmers be set at 70°-80°C for 45 minutes to 1 hour (maximum); tire performance degradation may occur if tires are subjected to repeated tire warming cycles, and/or temperatures/times in excess of these.

This chart excludes Daytona.

Width and Diameter are measured on recommended rim.

NON-DOT ROAD RACE
TECHNICAL DATA




TIRE MODEL	POS	SIZE	COMPOUND(S)	DURABILITY		REC. RIM (INCHES)	RIM RANGE	WIDTH (MM)	DIA	INFLATION PRESSURE (PSI)	
				MAX GRIP	MAX LIFE					COLD	HOT
MOTO3	FRONT	90/80R17	SOFT			2.5	2.15-2.5	88	578	26-28	30-33
	REAR	115/75R17	SOFT			3.5	2.75-3.5	113	601	28-30	30-33

Dunlop recommends that tire warmers be set at 70°-80°C for 45 minutes to 1 hour (maximum); tire performance degradation may occur if tires are subjected to repeated tire warming cycles, and/or temperatures/times in excess of these.

This chart excludes Daytona.

Width and Diameter are measured on recommended rim.

NON-DOT ROAD RACE
TECHNICAL DATA

TIRE MODEL	POS	SIZE	COMPOUND(S)	DURABILITY		REC. RIM	RIM RANGE	WIDTH	DIA	INFLATION PRESSURE (PSI)	
				MAX GRIP	MAX LIFE					COLD	HOT
KR189 (WET)	FRONT	95/70R17	WA			2.5	2.15-2.5	88	576	26-28	N/A
	FRONT	110/70R17	WA			3.0	2.75-3.5	116	588	30-33	N/A
	FRONT	120/70R17	WA			3.5	3.5-3.75	120	600	31-35	N/A
KR389 (WET)	REAR	115/70R17	WA			3.5	2.75-3.5	116	600	28-33	N/A
	REAR	140/65R17	WA			4.0	3.5-4.5	140	620	30-33	N/A
	REAR	165/55R17	WA			5.5	4.5-5.5	163	623	30-33	N/A
KR405 (WET)	REAR	190/60R17	WA			6.0	5.5-6.25	186	651	30-33	N/A

Dunlop recommends that tire warmers be set at 70°-80°C for 45 minutes to 1 hour (maximum); tire performance degradation may occur if tires are subjected to repeated tire warming cycles, and/or temperatures/times in excess of these. Dunlop does not recommend the use of tire warmers on rain tires.

This chart excludes Daytona.

Width and Diameter are measured on recommended rim.

NON-DOT ROAD RACE
TECHNICAL DATA

TIRE MODEL	POS	SIZE	COMPOUND(S)	DURABILITY		REC. RIM (INCHES)	RIM RANGE	WIDTH (MM)	DIA	INFLATION PRESSURE (PSI)	
				MAX GRIP	MAX LIFE					COLD	HOT
SPORTMAX SLICK	FRONT	120/75R17	R0 (Q) - 0516			3.5	3.5-3.75	117	611	30-32	34-36
			R3 (XS) - 0129								
			R5 (S) - 0097								
			R7 (M) - 0455								
	REAR	180/65R17	R3 (XS) - 0129			5.0	5.0-5.5	175	663	19-22	22-25
			R5 (S) - 0097								
			R7 (M) - 0455								
			R8 (H) - 0585								
	REAR	200/65R17	R0 (Q) - 0516			6.00	5.5-6.25	195	676	19-22	22-25
			R2 (SS) - 0197								
			R3 (XS) - 0129								
			R5 (S) - 0097								
R7 (M) - 0455											
R8 (H) - 0585											
KR448	FRONT	110/70R17	0129			3.0	2.5-3.5	108	593	32-36	34-38
	FRONT	120/70R17	0516			3.5	3.5-3.75	117	608	30-32	34-36
			0129								
			2662								
			7455								
			8477								
KR451	REAR	140/70R17	0443			4.0	3.5-4.0	140	628	22-24	26-28
	REAR	165/55R17	0197			5.0	4.5-5.25	165	629	22-24	24-26
			0455								
	REAR	180/60R17	0197			5.5	5.0-5.5	184	656	19-22	22-25
			0129								
			0097								
			0455								
			0585								
	REAR	200/60R17	0197			6.0	6.0-6.25	194	671	19-22	22-25
			0129								
			0097								
			0455								
0585											
KR151	FRONT	120/70R17	0129			3.5	3.5-3.75	118	603	30-32	34-36

Dunlop recommends that tire warmers be set at 70°-80°C for 45 minutes to 1 hour (maximum); tire performance degradation may occur if tires are subjected to repeated tire warming cycles, and/or temperatures/times in excess of these.
 This chart excludes Daytona.
 Width and Diameter are measured on recommended rim.